

View Online at <https://aerobasegroup.com/nsn/5320-01-612-3306>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.545 inches

Head Style:

Straight pan

Head Height:

Between 0.130 inches and 0.140 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.197 inches and 0.217 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.550 inches and 0.585 inches

Grip Length:

1.000 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Shear Strength:

24600 double pounds per square inch

Material:

Steel comp 8740 or steel comp 4140 or steel comp 4340

Material Specification:

Mil-s-6049 military specification single material response or ams 6322 assn standard single material response or ams 6382 assn standard single material response or ams 6415 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.