## NSN 5320-01-613-0070

Pin-rivet - Page 1 of 2



3a

**Thread Direction:** 

**Thread Class:** 

**Right-hand** 

## Fastener Length:

0.450 inches

#### Head Style:

Straight pan

#### Head Height:

Between 0.064 inches and 0.074 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.2177 inches and 0.2182 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.370 inches and 0.390 inches

#### Lubrication:

Cetyl alcohol

## **End Application:**

C-17 acft

#### Grip Length:

0.125 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.1900 inches

#### **Product Name:**

Pin-rivet, threaded-protruding hd, titanium

#### **Special Features:**

Head chamfered 40 degrees min/50 degrees maximum angle height of 0.029

#### Material:

Titanium alloy

## Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--



# NSN 5320-01-613-0070

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

