# NSN 5320-01-613-1408

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-613-1408

## Fastener Length:

Between 0.084 inches and 0.104 inches

#### Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.186 inches and 0.190 inches

#### Shank Style:

Straight w/radius chamfered tip

## Head Major Diameter:

Between 0.349 inches and 0.357 inches

## End Application:

5310-01-024-6299

## Features Provided:

Standard

## Shear Strength:

33000 single pounds per square inch

## **Countersink Angle:**

100.0 degrees

## Product Name:

Rivet, solid, c'sunk 100 deg, precision head, alum alloy

# **Special Features:**

Matl 2017-t4 is inactive for new design

# Material:

Aluminum alloy 2017

# Material Specification:

Qq-a-430, 2017-t4 federal specification single material response

# Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625, ty ii, cl 1 military specification single treatment response

#### Shelf Life:

N/a

# Unit Of Measure:

```
---
```

# Demilitarization:

No

Fiig:

A040a0

#### Mil-std (military Standard):

Mil-a-8625 spec.