NSN 5320-01-613-1823

Solid Rivet - Page 1 of 1

Mil-c-5541 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-613-1823

Fastener Length:
0.1325 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Head Height:
0.055 inches
Shank Diameter:
Between 0.155 inches and 0.159 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.282 inches and 0.290 inches
End Application:
5310-01-024-6299
Countersink Angle:
Between 99.50 degrees and 100.50 degrees
Product Name:
Rivet, solid, countersunk 100 degrees, precision head
Special Features:
Rivet has a raised teat on head. Teat has a maximum diameter of 0.030 inches. length of rivet is 0.1775 to 0.1975 inches. Color is
gold/yellow.
Heat Treatment:
T-4 solution heat treated
Material:
Aluminum alloy 2017
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541, class 1a, gold/yellow military specification single treatment response
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):