

View Online at <https://aerobasegroup.com/nsn/5320-01-613-9751>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.000 inches

Head Style:

Crown countersunk less than 135 degrees

Head Height:

Between 0.0612 inches and 0.0633 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.334 inches and 0.347 inches

Lubrication:

Cetyl alcohol

End Application:

C-17 aircraft

Grip Length:

0.625 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.1900 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, threaded, 100 degrees fl crown rivet hd

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 federal standard single material response or ams4928 federal standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Dps 4.50-197 (hi-kote 1 only) mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0