NSN 5320-01-614-6178

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-614-6178 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.887 inches **Head Style:** Straight pan **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.302 inches and 0.306 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.472 inches and 0.505 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.562 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 16000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 5380 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** 294 mfr ref single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5320-01-614-6178

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0