NSN 5320-01-614-7862

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-614-7862 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.41 inches and 1.43 inches **Head Style:** Straight pan **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.160 inches and 0.180 inches **Shank Diameter:** Between 0.3266 inches and 0.3276 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** C-5m aircraft **Grip Length:** Between 0.870 inches and 0.880 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 210000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 125000 single pounds per square inch Material: Nickel alloy 718 **Surface Treatment:** Cadmium **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-614-7862

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0