NSN 5320-01-614-9510

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-614-9510 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.052 inches and 1.072 inches **Head Style:** Straight pan **Head Height:** Between 0.037 inches and 0.047 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.242 inches and 0.262 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** C-5m aircraft **Grip Length:** Between 0.745 inches and 0.760 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 108000 single pounds per square inch **Special Features:** Mrc aatb: width across flats, noted with "evidence of broken edge across points." no dimensions provided Material: Steel comp e4340 **Surface Treatment:** Cadmium **Thread Series Designator:** Unjc Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-614-9510

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0