

View Online at <https://aerobasegroup.com/nsn/5320-01-615-1698>

Thread Class:

G3a

Fastener Length:

1.520 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

Lubrication:

Cetyl alcohol

End Application:

C-17a aircraft

Grip Length:

1.125 inches

Thread Size:

0.2500 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-riquet, threaded-100 degrees fl crown shear hd, titanium

Special Features:

Heat treat 95 ksi min; 160-180 ksi ftu per mil-h-81200

Heat Treatment:

Annealed

Material:

Titanium alloy

Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Dps 4.50-197 (hi-kote only) mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0