
# NSN 5320-01-615-2030

Pin-rivet - Page 1 of 2





# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

0.5750 inches

# Head Style:

Cooper's

#### **Head Height:**

Between 0.0449 inches and 0.0470 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1810 inches and 0.1840 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

0.270 inches

#### Lubrication:

Cetyl alcohol

## End Application:

C-17 aircraft

#### Grip Length:

0.250 inches

## Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

2000 pounds per square inch

## Thread Size:

0.1900 inches

#### **Countersink Angle:**

100.0 degrees

#### **Product Name:**

Pin-rivet, threaded

## Material:

Stainless steel

## **Material Specification:**

Ams5761 assn standard single material response or ams5737 assn standard single material response

#### Surface Treatment:

Passivate

#### **Surface Treatment Specification:**

Qq-p-35 federal standard single treatment response

# NSN 5320-01-615-2030

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

