## NSN 5320-01-615-2031



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-615-2031 **Thread Class:** G3a **Thread Direction:** Right-hand Fastener Length: 0.645 inches **Head Style:** Straight pan **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2802 inches and 0.2807 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.435 inches and 0.460 inches Lubrication: Cetyl alcohol **End Application:** C-17a aircraft **Grip Length:** 0.250 inches Thready Qty Per Inch (tpi): J28 **Thread Size:** 0.2500 inches **Product Name:** Pin-rivet, threaded-100 degrees fl crown shear hd, titanium **Special Features:** Heat treat 95 ksi min; 160-180 ksi ftu per mil-h-81200; finish w/chromamates Material: Titanium alloy uns r56400 **Surface Treatment:** Aluminum alloy **Surface Treatment Specification:** Dps 4.50-197 hi-kote 1 only mfr ref single treatment response **Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5320-01-615-2031

Pin-rivet - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A528u0