

View Online at <https://aerobasegroup.com/nsn/5320-01-615-2349>

**Thread Class:**

G3a

**Fastener Length:**

1.520 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2646 inches and 0.2651 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.3898 inches and 0.3948 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-17a aircraft

**Grip Length:**

1.125 inches

**Thread Size:**

0.2500 inches

**Countersink Angle:**

135.0 degrees

**Product Name:**

Pin-riquet, threaded-100 degrees fl crown shear hd, titanium

**Special Features:**

Heat treat 95 ksi min; 160-180 ksi ftu per mil-h-81200

**Heat Treatment:**

Annealed

**Material:**

Titanium alloy

**Material Specification:**

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

**Surface Treatment:**

Aluminum and chromate

**Surface Treatment Specification:**

Dps 4.50-197 (hi-kote only) mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0