NSN 5320-01-615-6007

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-615-6007 **Thread Class:** G3a **Thread Direction:** Right-hand Fastener Length: 1.707 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches **Chamfer Length:** 0.034 inches Lubrication: Cetyl alcohol **End Application:** C-5m rerp o-level fuselage pkg provisioning **Grip Length:** 1.312 inches Thready Qty Per Inch (tpi): J28 **Thread Size:** 0.2500 inches **Product Name:** Pin-threaded, protruding head, shear type, 431 stainless steel **Special Features:** Heat treat 125 ksi shear, 210-225 ksi tensile Material: Steel comp 431 **Material Specification:** Qq-s-763 federal standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-615-6007

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0