NSN 5320-01-615-6007

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-615-6007

Thread	Class:

G3a

Thread Direction:

Right-hand

Fastener Length:

1.707 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Chamfer Length:

0.034 inches

Lubrication:

Cetyl alcohol

End Application:

C-5m rerp o-level fuselage pkg provisioning

Grip Length:

1.312 inches

Thready Qty Per Inch (tpi):

J28

Thread Size:

0.2500 inches

Product Name:

Pin-threaded, protruding head, shear type, 431 stainless steel

Special Features:

Heat treat 125 ksi shear, 210-225 ksi tensile

Material:

Steel comp 431

Material Specification:

Qq-s-763 federal standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-615-6007

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

