

View Online at <https://aerobasegroup.com/nsn/5320-01-616-8764>

Thread Class:

3a

Thread Direction:

Right-hand

Head Style:

Flush countersunk

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-riquet, tapered, threaded

Head Major Diameter:

Between 0.376 inches and 0.381 inches

Tip Diameter:

Between 0.181 inches and 0.184 inches

Lubrication:

Solid film and cetyl alcohol

End Application:

Ng nav system

Grip Length:

Between 0.3075 inches and 0.3175 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

4350 pounds per square inch

Thread Size:

0.1900 inches

Shear Strength:

7060 double pounds per square inch

Countersink Angle:

100.0 degrees

Product Name:

Pin, threaded, hex point drive

Special Features:

Solid film lubricant per mil-I-46010 "kal-gard" type "fa" or hi-kote 2 only and cetyl alcohol lube; hex drive point is .0791/.0801 width across flats, .080/.100 deep; .104/.119 dia

Material:

Nickel alloy 718

Material Specification:

Ams5662 national specification single material response

Thread Series Designator:

Unjf

Specification Data:

1w025-03a063 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0