

View Online at <https://aerobasegroup.com/nsn/5320-01-617-0769>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Black

Fastener Length:

0.833 inches

Head Style:

Straight pan

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Chamfer Length:

0.031 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

C-5 reliability enhancement re-engining program

Grip Length:

0.438 inches

Thready Qty Per Inch (tpi):

B28

Min. Tensile Strength (psi):

4300 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

9300 double pounds per square inch

Product Name:

Protruding shear head titanium

Material:

Titanium alloy

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-shear specification 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0