

View Online at <https://aerobasegroup.com/nsn/5320-01-617-1373>

Thread Class:

M3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.947 inches and 0.967 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

C-5 reliability enhancement re-engining program

Grip Length:

0.562 inches

Thread Qty Per Inch (tpi):

B32

Min. Tensile Strength (psi):

2000 pounds per square inch

Thread Size:

0.188 inches

Shear Strength:

5380 double pounds per square inch

Countersink Angle:

100.0 degrees

Product Name:

Pin, flush, reduced

Special Features:

Color black on threads; 32 microinch finish

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-shear specification 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0