## NSN 5320-01-618-2112

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-618-2112 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.253 inches and 1.273 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.202 inches and 0.203 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.296 inches and 0.301 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Kc-135 acft **Grip Length:** Between 0.933 inches and 0.943 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Product Name:** Fastener Material: Titanium alloy uns r56400 **Surface Treatment:** Aluminum **Thread Series Designator:** Unjf Shelf Life:

N/a **Unit Of Measure:** 

## NSN 5320-01-618-2112

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0