NSN 5320-01-618-5984

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-618-5984 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.052 inches and 1.072 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.127 inches and 0.129 inches **Shank Diameter:** Between 0.326 inches and 0.327 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.472 inches and 0.505 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Kc-135 acft **Grip Length:** Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** Between 90.0 degrees and 100.0 degrees **Product Name:** Fastener Material: Titanium alloy uns r56400 **Surface Treatment:** Aluminum

Thread Series Designator: Unjf Shelf Life: N/a **Unit Of Measure:**

NSN 5320-01-618-5984

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0