

View Online at <https://aerobasegroup.com/nsn/5320-01-618-8086>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.753 inches and 0.773 inches

Head Style:

Straight pan

Head Height:

Between 0.064 inches and 0.074 inches

Shank Diameter:

Between 0.181 inches and 0.184 inches

Shank Style:

Stump

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Grip Length:

Between 0.433 inches and 0.443 inches

Width Across Flats:

Between 0.079 inches and 0.081 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

5380 double pounds per square inch

Thread Tolerance Class:

3a external

Product Name:

Pin, rivet, threaded, protruding tension head, hex-point drive

Material:

Steel

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or ams 6322 assn standard single material response or ams 6325 assn standard single material response or ams 6327 assn standard single material response or ams 6415 assn standard single material response or ams 6484 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2, federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.