

View Online at <https://aerobasegroup.com/nsn/5320-01-618-8086>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.753 inches and 0.773 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.064 inches and 0.074 inches

**Shank Diameter:**

Between 0.181 inches and 0.184 inches

**Shank Style:**

Stump

**Head Major Diameter:**

Between 0.357 inches and 0.377 inches

**Grip Length:**

Between 0.433 inches and 0.443 inches

**Width Across Flats:**

Between 0.079 inches and 0.081 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

5380 double pounds per square inch

**Thread Tolerance Class:**

3a external

**Product Name:**

Pin, rivet, threaded, protruding tension head, hex-point drive

**Material:**

Steel

**Material Specification:**

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or ams 6322 assn standard single material response or ams 6325 assn standard single material response or ams 6327 assn standard single material response or ams 6415 assn standard single material response or ams 6484 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2, federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.