

View Online at <https://aerobasegroup.com/nsn/5320-01-619-9649>

Thread Class:

3b

Thread Direction:

Right-hand

Fastener Length:

Between 0.7525 inches and 0.7725 inches

Head Style:

Straight pan

Head Height:

0.045 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

0.1875 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Collar Outside Diameter:

Between 0.318 inches and 0.322 inches

Collarheight:

Between 0.437 inches and 0.457 inches

Lubrication:

Cetyl alcohol

Collar Inside Diameter:

Between 0.208 inches and 0.212 inches

End Application:

1520-01-599-2203

Grip Length:

Between 0.4325 inches and 0.4425 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Collar Style:

Threaded break off type

Heat Treatment:

T-6 solution heat treated collar

Material:

Steel body

Material Specification:

Qq-a-430 federal specification single material response or qq-a-225/6 federal specification single material response collar

Surface Treatment:

Cadmium body

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response body

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.