## NSN 5320-01-619-9731

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-619-9731 **Thread Class:** 3b **Thread Direction:** Right-hand Fastener Length: 0.762 inches **Head Style:** Straight pan **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Collar Outside Diameter:** Between 0.303 inches and 0.307 inches Collarheight: Between 0.437 inches and 0.457 inches Lubrication: Cetyl alcohol **Collar Inside Diameter:** Between 0.208 inches and 0.212 inches **End Application:** 1520-01-599-2203 **Grip Length:** Between 0.432 inches and 0.442 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 body **Material Specification:** Mil-s-5000 military specification 1st material response body **Surface Treatment:** Cadmium Shelf Life:

N/a

## NSN 5320-01-619-9731

Pin-rivet - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.