## NSN 5320-01-620-7103

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

1.008 inches

**Thread Direction:** 

Fastener Length:

СЗа



View Online at https://aerobasegroup.com/nsn/5320-01-620-7103

Head Style:
Flush countersunk
Width Between Flats:
0.189 inches
Shank Diameter:
Between 0.3115 inches and 0.3120 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
0.602 inches
End Application:
F-22 raptor
Grip Length:
0.427 inches
Thready Qty Per Inch (tpi):
U24
Min. Tensile Strength (psi):
12300 pounds per square inch
Thread Size:
0.3125 inches
Shear Strength:
19160 double pounds per square inch
Countersink Angle:
100.0 degrees
Product Name:
Eddie-bolt 2 pin 100 degrees flush tension head
Material:
Nickel alloy 718
Material Specification:
Ams5662 federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Ams2700 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5320-01-620-7103

Pin-rivet - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0