

View Online at <https://aerobasegroup.com/nsn/5320-01-620-7103>

**Thread Class:**

C3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.008 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

0.189 inches

**Shank Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

0.602 inches

**End Application:**

F-22 raptor

**Grip Length:**

0.427 inches

**Thready Qty Per Inch (tpi):**

U24

**Min. Tensile Strength (psi):**

12300 pounds per square inch

**Thread Size:**

0.3125 inches

**Shear Strength:**

19160 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Product Name:**

Eddie-bolt 2 pin 100 degrees flush tension head

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams2700 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0