

View Online at <https://aerobasegroup.com/nsn/5320-01-620-7531>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.9675 inches and 0.9875 inches

Head Style:

Straight pan

Head Height:

Between 0.064 inches and 0.074 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.6825 inches and 0.6925 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.1900 inches

Shear Strength:

7060 double pounds per square inch

Product Name:

Pin, protruding tension head

Special Features:

Cetyl alcohol lube per hi-shear specification 305 or as87132.

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-shear specification 294 mfr ref single treatment response or nas4006 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0