

View Online at <https://aerobasegroup.com/nsn/5320-01-621-0090>

**Thread Class:**

C3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.660 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

0.120 inches

**Shank Diameter:**

0.1881 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.350 inches

**Hole Depth:**

0.140 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

Rq-4a

**Grip Length:**

0.375 inches

**Thready Qty Per Inch (tpi):**

U32

**Min. Tensile Strength (psi):**

3180 pounds per square inch

**Thread Size:**

0.1900 inches

**Shear Strength:**

5380 double pounds per square inch

**Countersink Angle:**

Between 99.0 radians and 101.0 radians

**Product Name:**

Eddie spline pin, 100 degrees flush tension head

**Special Features:**

Spline-lok recess

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Afs specification +5103 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0