## NSN 5320-01-622-7657

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-622-7657

Head Style:
Universal
Head Height:
Between 0.054 inches and 0.064 inches
Shank Diameter:
Between 0.125 inches and 0.129 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.238 inches and 0.262 inches
Grip Length:
Between 0.194 inches and 0.224 inches
Features Provided:
Self-locking Self-locking
Product Name:
Rivet, blind, protruding head, mechanically locked spindle, bulbed style a, class 1, code b and e
Material:
Steel comp 632 or iron alloy 660 stem
Material Specification:
Ams5737 national std/spec 1st material response or astm a493 assn standard 2nd material response or astm a493 assn standard 3rd
material response or astm a493 assn standard 4th material response or astm a493 assn standard 5th material response or astm a493
assn standard 6th material response or astm a493 assn standard 7th material response or astm a493 assn standard 8th material response
or astm a493 assn standard 9th material response grip
Surface Treatment:
Passivate stem
Surface Treatment Specification:
Mil-dtl-5541, ty i, cl 1a military specification single treatment response sleeve
Specification Data:
80205-nas9301 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
<del>_</del>
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-dtl-5541 spec.