NSN 5320-01-622-7657

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-622-7657

| Head Style: |
|---|
| Universal |
| Head Height: |
| Between 0.054 inches and 0.064 inches |
| Shank Diameter: |
| Between 0.125 inches and 0.129 inches |
| Shank Style: |
| Self-plugging mechanically locked stem |
| Head Major Diameter: |
| Between 0.238 inches and 0.262 inches |
| Grip Length: |
| Between 0.194 inches and 0.224 inches |
| Features Provided: |
| Self-locking Self-locking |
| Product Name: |
| Rivet, blind, protruding head, mechanically locked spindle, bulbed style a, class 1, code b and e |
| Material: |
| Steel comp 632 or iron alloy 660 stem |
| Material Specification: |
| Ams5737 national std/spec 1st material response or astm a493 assn standard 2nd material response or astm a493 assn standard 3rd |
| material response or astm a493 assn standard 4th material response or astm a493 assn standard 5th material response or astm a493 |
| assn standard 6th material response or astm a493 assn standard 7th material response or astm a493 assn standard 8th material response |
| or astm a493 assn standard 9th material response grip |
| Surface Treatment: |
| Passivate stem |
| Surface Treatment Specification: |
| Mil-dtl-5541, ty i, cl 1a military specification single treatment response sleeve |
| Specification Data: |
| 80205-nas9301 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| _ |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-dtl-5541 spec. |
| |