

View Online at <https://aerobasegroup.com/nsn/5320-01-623-6774>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.67 inches

**Head Style:**

Crown countersunk less than 135 degrees

**Head Height:**

Between 0.075 inches and 0.078 inches

**Width Between Flats:**

Between 0.197 inches and 0.217 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.555 inches and 0.560 inches

**Lubrication:**

Dry film and cetyl alcohol

**End Application:**

A-10 wrp

**Grip Length:**

1.125 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-rivet, threaded, shear, 100 c'sunk head, hex pt dr

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams 2700 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0