

View Online at <https://aerobasegroup.com/nsn/5320-01-623-7370>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.562 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.045 inches and 0.055 inches

**Width Between Flats:**

Between 0.0806 inches and 0.1885 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.295 inches and 0.315 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

Various c-5 aircraft

**Grip Length:**

Between 1.120 inches and 1.130 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

125000 single pounds per square inch

**Product Name:**

Protruding shear head, type 431, stainless steel, cad plated

**Material:**

Steel comp 431

**Material Specification:**

Mil-s-18732 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-18732 spec.