## NSN 5320-01-623-7808

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-623-7808



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.573 inches and 1.593 inches

### Head Style:

Straight pan

#### **Head Height:**

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### **End Application:**

Various c-5 aircraft

## Grip Length:

1.563 inches

#### Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

#### Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp 431

#### Material Specification:

Mil-s-18732 military specification single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-623-7808

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

