NSN 5320-01-623-7825

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-623-7825 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.573 inches and 1.593 inches **Head Style:** Straight pan **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Various c-5 aircraft **Grip Length:** 1.688 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-623-7825

Pin-rivet - Page 2 of 2



ι	Jn	it	Of	Measure:	•

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.