NSN 5320-01-623-8659

Solid Rivet - Page 1 of 1

Mil-std (military Standard):

Mil-a-8625 spec.



| View Online at https://aerobasegroup.com/nsn/5320-01-623-8659 |
|---|
| Fastener Length: |
| Between 1.115 inches and 1.135 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.186 inches and 0.190 inches |
| Shank Style: |
| Straight w/radius chamfered tip |
| Head Major Diameter: |
| Between 0.349 inches and 0.357 inches |
| Grip Length: |
| Between 0.834 inches and 0.854 inches |
| Shear Strength: |
| 3700 single pounds per square inch |
| Countersink Angle: |
| Between 99.5 degrees and 100.5 degrees |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-430 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type ii, class 1, dichromate military specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |