NSN 5320-01-624-2230

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-624-2230 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.662 inches **Head Style:** Straight pan **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.181 inches and 0.184 inches **Shank Diameter:** 0.187 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.397 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.372 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 5100 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 12260 double pounds per square inch Material: Stainless steel **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi-shear specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-01-624-2230

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0