NSN 5320-01-624-6753

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-624-6753 **Thread Class:** За **Thread Direction:** Right-hand **Head Style:** Flush countersunk **Hole Diameter:** 0.015 inches **Shank Diameter:** 0.3897 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.444 inches **Hole Depth:** Between 0.2535 inches and 0.2735 inches **Tip Diameter:** Between 0.3053 inches and 0.3105 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and cetyl alcohol **End Application:** F-15sa **Grip Length:** 0.6300 inches Thready Qty Per Inch (tpi): N24 **Thread Size:** 0.312 inches **Countersink Angle:** 100.0 degrees **Special Features:** Hole threads unjc, class 3b, 32 threads, thread depth 0.300 in. Min/0.345 in. Max Material: Stainless steel **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal standard single treatment response

Thread Series Designator: Unjf

Shelf Life:

N/a

NSN 5320-01-624-6753

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0