

View Online at <https://aerobasegroup.com/nsn/5320-01-625-1154>

Thread Class:

E3a

Thread Direction:

Right-hand

Fastener Length:

1.545 inches

Head Style:

Straight pan

Head Height:

Between 0.130 inches and 0.140 inches

Width Between Flats:

Between 0.197 inches and 0.217 inches

Shank Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.530 inches and 0.565 inches

Chamfer Length:

Between 0.065 inches and 0.075 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

C-5 avionics mod program; rerp o-level pylon package

Grip Length:

0.545 inches

Thready Qty Per Inch (tpi):

N24

Min. Tensile Strength (psi):

14000 pounds per square inch

Thread Size:

0.3750 inches

Shear Strength:

21000 double pounds per square inch

Product Name:

Hi-lok pin protruding head

Material:

Iron alloy 660

Material Specification:

Ams5737 federal specification single material response or ms5731 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear specification 258 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0