

View Online at <https://aerobasegroup.com/nsn/5320-01-625-2962>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.075 inches

**Head Style:**

Flush countersunk

**Head Height:**

0.046 inches

**Width Between Flats:**

0.080 inches

**Shank Diameter:**

0.189 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

0.300 inches

**Lubrication:**

Solid film or dry film

**End Application:**

Afc 615

**Grip Length:**

0.750 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

125000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-rivet, threaded, shear, 100 degrees c'sunk, hex point drive

**Material:**

Steel comp xm-13

**Material Specification:**

Astm 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams-qq-p-35 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0