# NSN 5320-01-625-8125

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-625-8125

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

1.318 inches

## Head Style:

Flush countersunk

#### Shank Diameter:

0.3403 inches

Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.458 inches and 0.508 inches

#### **Tip Diameter:**

Between 0.3053 inches and 0.3105 inches

#### Lubrication:

Dry film and cetyl alcohol

#### **End Application:**

F-15sa

#### Grip Length:

0.937 inches

#### Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.3125 inches

# Shear Strength:

95000 single pounds per square inch

## Countersink Angle:

100.0 degrees

# Product Name:

Fastener, shear, 100 degree standard flush head, tapered shank

## Material:

Titanium alloy

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 5320-01-625-8125

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

