
# NSN 5320-01-626-8716

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

0.750 inches

#### **Head Style:**

Flush countersunk

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.306 inches and 0.313 inches

#### Lubrication:

Dry film or solid film

### **End Application:**

F-15sa

#### Grip Length:

0.438 inches

### Thready Qty Per Inch (tpi):

32

## Thread Size:

0.1640 inches

## **Countersink Angle:**

100.0 degrees

# Product Name:

Pin, rivet, threaded-tension, 100 degrees c-sunk, hex point drive

## Material:

Steel comp xm-13

# Material Specification:

Ams 5629 federal standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-626-8716

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

