# NSN 5320-01-627-1105

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-627-1105

## Fastener Length:

Between 0.302 inches and 0.322 inches

### Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Head Height:

Between 0.003 inches and 0.005 inches

### Shank Diameter:

Between 0.124 inches and 0.127 inches

### Shank Style:

Straight w/radius chamfered tip

### Head Major Diameter:

Between 0.188 inches and 0.195 inches

### Head Minor Diameter:

0.174 inches

### **Countersink Height:**

0.029 inches

### End Application:

F-18 e/f aircraft

### **Countersink Angle:**

Between 70.0 degrees and 130.0 degrees

## Heat Treatment:

T-4 solution heat treated

## Material:

Aluminum alloy 2117

## Surface Treatment:

Dichromate

## Surface Treatment Specification:

Anodize per mil-a-8625, type ii, class 1 (dichromate seal), color: yellow military specification single treatment response

## Specification Data:

80205-mil-r-5674 government specification and 80205-nas1097 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

```
---
```

## Demilitarization:

No

Fiig:

A040a0

#### Mil-std (military Standard):

Mil-a-8625 spec.