NSN 5320-01-627-1105

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-627-1105

Fastener Length:
Between 0.302 inches and 0.322 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.124 inches and 0.127 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.188 inches and 0.195 inches
Head Minor Diameter:
0.174 inches
Countersink Height:
0.029 inches
End Application:
F-18 e/f aircraft
Countersink Angle:
Between 70.0 degrees and 130.0 degrees
Heat Treatment:
T-4 solution heat treated
Material:
Aluminum alloy 2117
Surface Treatment:
Dichromate
Surface Treatment Specification:
Anodize per mil-a-8625, type ii, class 1 (dichromate seal), color: yellow military specification single treatment response
Specification Data:
80205-mil-r-5674 government specification and 80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-a-8625 spec.