

View Online at <https://aerobasegroup.com/nsn/5320-01-627-2955>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.295 inches

**Head Style:**

Crown countersunk less than 135 degrees

**Head Height:**

Between 0.1309 inches and 0.1329 inches

**Width Between Flats:**

Between 0.1582 inches and 0.1617 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.672 inches and 0.684 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-17a globemaster iii

**Grip Length:**

0.750 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.3750 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-riquet, threaded-100 degrees fl crown rivet head

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 federal specification single material response or ams4967 federal specification single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0