NSN 5320-01-627-3667

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-627-3667

| View Online at https://aerobasegroup.com/nsn/5320-01-627-3667 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Fastener Length: |
| 1.223 inches |
| Head Style: |
| Crown countersunk less than 135 degrees |
| Head Height: |
| Between 0.1309 inches and 0.1329 inches |
| Width Between Flats: |
| Between 0.1582 inches and 0.1617 inches |
| Shank Diameter: |
| Between 0.3740 inches and 0.3745 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.672 inches and 0.684 inches |
| Lubrication: |
| Cetyl alcohol |
| End Application: |
| C-17a globemaster iii |
| Grip Length: |
| 0.688 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.3750 inches |
| Countersink Angle: |
| 100.0 degrees |
| Product Name: |
| Pin-rivet, threaded-100 degrees fl crown rivet head |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams4967 federal specification single material response or ams4928 federal specification single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5320-01-627-3667

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

