
## NSN 5320-01-628-9310

Pin-rivet - Page 1 of 2





## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

1.1375 inches

#### **Head Style:**

Flush countersunk

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

0.190 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

#### Lubrication:

Dry film and solid film

#### **End Application:**

F/a-18

#### Grip Length:

0.8125 inches

#### Thready Qty Per Inch (tpi):

32

#### **Thread Size:**

0.190 inches

#### **Countersink Angle:**

100.0 degrees

#### **Criticality Code Justification:**

Agav

## Product Name:

Pin-rivet, threaded, shear, 100 degree c'sunk head, hex point drive

## Material:

Steel comp xm-13

## Material Specification:

A, s 5629 ph13-8mo assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Ams 2700 assn standard single treatment response

## **Thread Series Designator:**

Unjf

# NSN 5320-01-628-9310

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

