

View Online at <https://aerobasegroup.com/nsn/5320-01-628-9316>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.3325 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

0.250 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.3898 inches and 0.3948 inches

**Lubrication:**

Dry film and solid film

**End Application:**

F/a-18

**Grip Length:**

0.9375 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Countersink Angle:**

100.0 degrees

**Criticality Code Justification:**

Agav

**Product Name:**

Pin-rivet, threaded, shear, 100 degree c'sunk head, hex point drive

**Material:**

Steel comp xm-13

**Material Specification:**

A, s 5629 ph13-8mo assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams 2700 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0