NSN 5320-01-628-9316



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-628-9316 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.3325 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** 0.250 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3898 inches and 0.3948 inches Lubrication: Dry film and solid film **End Application:** F/a-18 **Grip Length:** 0.9375 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification:** Agav **Product Name:** Pin-rivet, threaded, shear, 100 degree c'sunk head, hex point drive Material: Steel comp xm-13 **Material Specification:** A, s 5629 ph13-8mo assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Ams 2700 assn standard single treatment response **Thread Series Designator:** Unjf

NSN 5320-01-628-9316

Pin-rivet - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0