NSN 5320-01-629-1248

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-629-1248

| view Offilitie at https://aerobasegroup.com/hsh/3320-01-023-1240 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Fastener Length: |
| Between 0.885 inches and 0.905 inches |
| Head Style: |
| Crown countersunk less than 135 degrees |
| Head Height: |
| Between 0.0852 inches and 0.0873 inches |
| Width Between Flats: |
| Between 0.0947 inches and 0.0967 inches |
| Shank Diameter: |
| Between 0.2646 inches and 0.2651 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.454 inches and 0.466 inches |
| Lubrication: |
| Cetyl alcohol |
| End Application: |
| C-17a |
| Grip Length: |
| Between 0.495 inches and 0.505 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.2500 inches |
| Countersink Angle: |
| 100.0 degrees |
| Product Name: |
| Pin-rivet, threaded-100 degrees fl crown head |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams4928 federal standard single material response or ams4967 federal standard single material response |
| Surface Treatment: |
| Aluminum and chromate |
| Surface Treatment Specification: |
| Dps 4.50-197 (hi-kote 1 only) mfr ref single treatment response |
| Thread Series Designator: |
| Unjf |

NSN 5320-01-629-1248

Pin-rivet - Page 2 of 2



| _ | | | | | | |
|---|----|----|---|----|---|---|
| C | he | 14 | | iŧ | 0 | • |
| J | | | _ | | ㄷ | - |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0