

View Online at <https://aerobasegroup.com/nsn/5320-01-629-1248>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.885 inches and 0.905 inches

Head Style:

Crown countersunk less than 135 degrees

Head Height:

Between 0.0852 inches and 0.0873 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2646 inches and 0.2651 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.454 inches and 0.466 inches

Lubrication:

Cetyl alcohol

End Application:

C-17a

Grip Length:

Between 0.495 inches and 0.505 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.2500 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, threaded-100 degrees fl crown head

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 federal standard single material response or ams4967 federal standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Dps 4.50-197 (hi-kote 1 only) mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0