

View Online at <https://aerobasegroup.com/nsn/5320-01-629-1248>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.885 inches and 0.905 inches

**Head Style:**

Crown countersunk less than 135 degrees

**Head Height:**

Between 0.0852 inches and 0.0873 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2646 inches and 0.2651 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.454 inches and 0.466 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-17a

**Grip Length:**

Between 0.495 inches and 0.505 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.2500 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-riquet, threaded-100 degrees fl crown head

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 federal standard single material response or ams4967 federal standard single material response

**Surface Treatment:**

Aluminum and chromate

**Surface Treatment Specification:**

Dps 4.50-197 (hi-kote 1 only) mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0